



White Sun

a futuristic approach to floor finish

White Sun is Spartan's futuristic high gloss finish with 18% solids. It teams an economical formula with optical enhancers, autofocus gloss and clarity.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
 1110 Spartan Drive
 Maumee, OH 43537
 1-800-537-8990
 www.spartanchemical.com

GLOSS AND AUTOFOCUS CLARITY:

White Sun is the futuristic approach to floor finishing. It diminishes the look of imperfections upon application, creating a better than ever appearance. Gloss and clarity come into focus automatically enhancing the overall look of your floors while intensifying the depth with crystal clear transparency.

WHITER AND BRIGHTER:

White Sun floor finish leaves a noticeably clearer and brighter appearance than competitive brands. It provides depth of gloss without yellowing or darkening undertones that muddy the finish. The floor's actual color and characteristics reflect through the finish, enhancing the original attributes of the flooring.

QUICK BUILD AND LEVELING:

Excellent leveling and quick dry time provides a mistake-proof application that quickly builds without developing mop marks or ridges.

PROTECTION AND STAMINA:

Advanced raw materials combine to form a finish with exemplary protection and stamina. The unique formula is a combination of an acrylic polymer emulsion backbone and ionic cross-linked bonding to provide a tough, durable and protective finish.

UL APPROVED:

Independent testing for slip resistance by Underwriter Laboratories confirms the static coefficient of friction of White Sun meets or exceeds 0.5 as determined by UL-410.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

INITIAL APPLICATION:

1. Completely strip all old wax or floor finish with a Spartan floor finish remover.
2. Remove the stripping solution and follow with two to three clear water rinses.
3. When flooring is old, abused or damaged, we recommend two coats of a Spartan Sealer, although White Sun can be used as a self-sealing finish.
4. Apply White Sun in a uniform coat. Let dry thoroughly for 30 to 40 minutes until surface is dry to the touch. Apply subsequent coats in the same manner. Three to five coats are recommended.

MAINTENANCE:

Routine: Dust mop with Spartan Dust Mop/Dust Cloth Treatment™ and damp mop with a Spartan neutral cleaner.

Periodic: Dust mop with Spartan Dust Mop/Dust Cloth Treatment™ and damp mop with a Spartan neutral cleaner. To repair traffic areas between finish applications, use a Spartan spraybuff or restorer. Traffic lanes may be recoated as necessary.

As Needed: Deep scrub and recoat; or completely strip, reseal if necessary and reapply White Sun.

NOTE: For best results always use Spartan floor cleaners and strippers.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATIONS:

Total Solids – 25.8%
 Non-Volatile Solids – 18%
 pH (Concentrate) – 8.0 – 9.0

Stability

- a. Storage @24°C/75°F – One year minimum
- b. Accelerated @49°C/120°F – 30 days minimum
- c. Freeze/Thaw – Can withstand three cycles

Gloss (Gardner)

- a. 1 coat – 90
- b. 2 coats – 93

COVERAGE:

Up to 3,000 square feet per gallon depending on application method and porosity of floor.



Distributed by:

PACKAGING	
405060	275-gallon totes
405055	55-gallon drum
405030	30-gallon drum
405015	15-gallon drum
405005	5-gallon pail
405004	1-gallon (4 per case)



Label copy is provided in English, Spanish, and French. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Product Available Worldwide. For institutional and industrial use only.

© SCC 5/11 L4050