



# BETWEEN THE LINES™

**grout sealer**

One coat is all it takes to seal out soils and stains from grout. Between the Lines™ grout sealer creates a water-proof barrier to dirt, water, and oil-based stains. Easily applied, the water-based formula creates an invisible barrier on the grout of ceramic, porcelain, and natural stone flooring and surfaces.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.  
 1110 Spartan Drive  
 Maumee, OH 43537  
 1-800-537-8990  
 www.spartanchemical.com

**FEATURES & BENEFITS:**

- One-coat application seals and protects
- Easy to use, water based formula
- Protects against dirt and oil-based stains
- Makes cleaning easier
- Deep-sealing formula keeps grout looking newer longer
- Designed for grout on natural stone, ceramic and porcelain tile

**DIRECTIONS FOR USE:**

Use only as directed. Some individuals may be sensitive to ingredients in this product. Before use, read entire product label and MSD sheet. If questions remain, consult your employer or a physician. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

**Note:** For interior use only. Not for use in areas of constant water exposure, such as showers. Do not apply product by spraying.

**Before using:** Allow new grout installations to cure for at least 72 hours prior to application. Be sure surface is clean, thoroughly dry and free of waxes and coatings. Test in an inconspicuous area with a 24-hour cure time to determine ease of application and desired results.

1. Clean surface with the appropriate Spartan industrial cleaner. Allow to dry.
2. Do not dilute. Thoroughly wet grout surface. Allow sealer to completely penetrate the grout lines.  
**For horizontal surfaces:** Pour directly on surface and spread evenly using a squeegee.  
**For vertical surfaces:** Wet foam brush and apply directly to grout lines. Continue to apply until no longer absorbed.
3. Allow to dry 30-60 minutes depending on porosity and conditions.
4. Do not allow foot traffic until completely dry.
5. After full cure (24 hours), wet clean tile to remove any residual product on tile surfaces.

**COVERAGE:**

Unglazed or porous tile – ~500 sqft/gal  
 Glazed or nonporous tile – 2000 sqft/gal or more

**SPECIFICATIONS:**

Specific Gravity – 1.001  
 pH – 4.0 - 5.0  
 Stability – Product separation is normal with age. Easily shake to redistribute prior to use.



**Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting [www.spartanchemical.com](http://www.spartanchemical.com).**



Distributed by:

PACKAGING	
408903	1-quart (12 per case)
408904	1-gallon (4 per case)



**GUARANTEE:** Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.