



AquaSport[®] 2-Part Wood Floor Finish

water-based urethane

Spartan's AquaSport 2-Part Wood Floor Finish is a water-based urethane wood floor finish. It dries quickly and is an ideal choice for sport wood floors and/or any high traffic wood floors where extreme durability and superior color are in order. This premium finish highlights the natural beauty of wood, amplifying the wood's characteristics without yellow undertones.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, OH 43537
1-800-537-8990
www.spartanchemical.com

PRODUCT FEATURES
WHY A 2-PART FINISH?

The catalyst component of AquaSport 2-Part Wood Floor Finish provides extra strength and durability, while allowing for exceptional flow and leveling characteristics. The catalyst also helps AquaSport 2-Part Wood Floor Finish to more quickly develop full resistance characteristics. It performs first rate in its ability to resist scuffs, marring, and accidental spills.

EASY TO MAINTAIN/EASY CLEAN-UP

Spartan's AquaSport 2-Part Wood Floor Finish provides long lasting finish protection that is easy to maintain. Product is easy to clean up with AquaSport Wood Floor Cleaner or water.

MEETS *OTC AND CALIFORNIA VOC (VOLATILE ORGANIC COMPOUNDS) EMISSION LEVELS

The extremely low VOC level meets the State of California and The Ozone Transport Commission VOC emission regulation. The low VOC level creates a nearly odorless finish that has a light pleasant fragrance. AquaSport 2-Part Wood Floor Finish is non-flammable.

**The (OTC) The Ozone Transportation Commission is a multi-state organization whose main focus is to develop regional solutions to the ground-level ozone problem in the Mid-Atlantic and Northeast region of the US.*

RECOMMENDED AREAS FOR APPLICATION

- Sports Floors: MFMA approved for gyms, exercise and aerobic floors, racquetball, handball and squash courts.
- Education: gymnasium, lounges, libraries, offices, and stages.
- Institutional: health care facilities, hospitals, nursing homes, and physicians' offices.
- Commercial: offices, retail sales floors, hotels & motels, restaurants, private clubs, museums.
- Residential: kitchens, entries, great rooms and family rooms.



Distributed by:

RECOMMENDED BUILD

The 2-part waterborne formula provides a gloss finish in two-to-three coats while enhancing the natural beauty of wood floors. AquaSport 2 Part Wood Floor Finish can be used in conjunction with AquaSport Wood Floor Sanding Seal to build a water-based coating on bare wood.

DIRECTIONS FOR USE

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

IMPORTANT NOTES

Use product as supplied. Do not thin product. Apply with a clean, designated waterborne applicator. Always provide adequate ventilation during any coating process. Never apply over waxes and or polishes.

APPLICATION EQUIPMENT

Easy application is achieved with Padco's "Big Foot Floor Coater" (heavy or light weighted T-Bars), an on-board tank release type applicator such as an E-Z Way or a lamb's wool type applicator. Apply finish in parallel lines, with the direction of the boards. Always apply thin coats. Work out puddles and ridgelines.

SPECIFICATION DATA:

PART A

Total Active Ingredients 39.5%

Appearance light tan

Odor resinous odor

Weight per gallon 8.73 lbs./gal. Flash point (T.C.C.) ->215°F

Stability

- a. Shelf life at 21°C/70°F - One year
- b. Freeze/Thaw - can withstand one cycle
- c. Accelerates at 49°C/120°F - 30 days

PART B

Total Active Ingredients 100%

Appearance clear pale yellow liquid

Odor resinous odor

Weight per gallon 8.91 lbs./gal. Flash point (T.C.C.) - >200°F

Stability of unopened container

- a. Shelf life at 21°C/70°F - One year
- b. Freeze/Thaw - can withstand one cycle
- c. Accelerates at 49°C/120°F - 30 days

PARTS A AND B

Non-Volatile Solids 30%

Coverage - 800 1000 ft.2/gal.

VOC Content less than 275 grams per liter.

NOTE: Typical high school basketball court (playing area) is 4,200 sq. ft. outside court boundaries will add to this significantly.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.



PACKAGING	
583400	5-gallon pail
583104	1-gallon (4 per case)

Label copy is provided in English, Spanish, and French. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.

For institutional and industrial use only.

© SCC 6/11 L5835